

LED Lamps • Corn & Horizontal 180° (PL 2pin/4pin-G23/24 & E26)



Watts	Lamp Type	Base	Item No.	Item Code	Color Kelvins	Initial Lumens	CRI	Volts	Dim	IP	Power Factor	Beam Angle	Dimensions (mm)	Equivalent Watts
5W	PL 180°	E26/ G23/G24	U/R	5PL/LED/180°/**	2700-6500	500-650	80	100-277	N	IP53	>0.9	180°	34xL120	10W PLC
7W			U/R	7PL/LED/180°/**	2700-6500	700-850	80	100-277	N	IP53	>0.9	180°	34xL142	13W PLC
9W			U/R	8PL/LED/180°/**	2700-6500	800-950	80	100-277	N	IP53	>0.9	180°	34xL157	18W PLC
11W			U/R	9PL/LED/180°/**	2700-6500	900-1050	80	100-277	N	IP53	>0.9	180°	34xL176	26W PLC
5W	PL 360°	E26/ G23/G24	U/R	5PL/LED/360°/**	2700-6500	400-500	80	100-240 or 277	N	IP53	>0.9	360°	41xL115	10W PLT
9W			U/R	9PL/LED/360°/**	2700-6500	700-850	80	100-240 or 277	N	IP53	>0.9	360°	41xL138	18W PLT
11W			U/R	11PL/LED/360°/**	2700-6500	1100-1250	80	100-240 or 277	N	IP53	>0.9	360°	51xL126	26W PLT
15W			U/R	15PL/LED/360°/**	2700-6500	1300-1400	80	100-240 or 277	N	IP53	>0.9	360°	51xL146	32/46 PLT

- Avg Rate Hrs: 50,000
- SMD2835 Epistar LED

****OPTIONS:**

- Diffuser: Clear / Opal
- Color (Kelvins): 2700, 4100, 5000, 6500
- Base: G24D, G24Q, G23-2, Gx23-2, E27, E26, B22

1 YEAR WARRANTY / CE RoHS

